

4B-1000

Magnetic Contact

Product Overview

The 4B-1000 is part of Elmdene's extensive range of magnetic contacts. It is a flush mounted 'pencil' type with potted cable (standard 10m length). It is ideal for use in both domestic and commercial installations in both single or multiple door configurations.

Constructed from plastic with a brass capped flange the 4B-1000 has an operating gap of 10mm.

Dimensions: 12F x 7.5D x 34L (mm)

The 4B range is designed to meet the requirements of EN50131-2-6:2008 Grade 2 and Environmental Class III.

Like all Elmdene magnetic contacts, the 4B is constructed from high quality materials and is easy to install, set up and commission with any intruder panel.

Features

- Plastic / Brass construction
- Pencil Style (7.5mm)
- Sleek and symmetrical design
- Push fit installation
- Environmental Class III
- 5 year warranty



Part Numbers

Part No
4B-1000

Technical Information

Operating gap	10mm
Material	Rhodium
Power handling	10VA
Voltage rating	100V dc, 150V ac max
Current rating - switch	1.0A max
Current rating - carry	1.5A max
Resistance	100m Ω
Operating life	> 100 x 10 ⁶

Product Dimensions

Flange: 12mm
Diameter: 7.5mm
Length: 34mm

Approvals

CE

