



FOR IN-HOUSE SECURITY MANAGERS

**The ultimate intruder alarm system for
commerce and industry**

Galaxy PC Packages

Galaxy User Management Suite

The Galaxy User Management Suite software has been developed specifically for in-house Security Managers. This software provides a user-friendly interface to key functions of the Galaxy security system allowing essential changes and amendments resulting from personnel changes or opening hours to be made, ensuring smooth and continuous day-to-day operation.

The software provides access to:

- User code management
- Event log copying
- Time and date change
- Virtual keypad for real-time control*
- Holiday period changes
- Summer time date change

User Management Suite can connect to Galaxy security systems via the following communications media:

For remote Galaxy sites allowing communication with multiple control panels:

- PSTN telephone line (using the Galaxy Telecom Module)
- ISDN line (using the Galaxy ISDN Module)*
- 10BaseT Ethernet (TCP/IP) local and wide area networks (using the Galaxy Ethernet Module)*

For local Galaxy sites:

- A dedicated connection to a single Galaxy control panel via the Galaxy RS232 Module

The Galaxy User Management Suite menu options provide the operator with a comprehensive range of features that allow site data be copied to and stored on the controlling PC or modified overwritten to control panels.

Operation control features

- Programmable user functions
- System and door access event log copying
- Displaying and printing of selected event log categories
- Off-line data programming
- Password protected access to Galaxy panels
- Password protected access to User Management Suite
- Single local site servicing
- Multiple remote site servicing
- Copy protection device (dongle) version available

Galaxy Event Monitoring

The Galaxy Event Monitoring software has been specifically designed to present system events and alarm activations to the operator in a clear, precise and detailed manner.

Galaxy Alarm Monitoring can connect to Galaxy security systems via the following communications media.

For remote Galaxy sites, allowing communication with multiple control panels:

- PSTN telephone line (using the Galaxy Telecom Module)
 - ISDN line (using the Galaxy ISDN Module)*
 - 10BaseT Ethernet (TCP/IP) local and wide area networks (using the Galaxy Ethernet Module)*
- There are two references to each of the above.

For local Galaxy sites:

- A dedicated connection to a single Galaxy control panel Galaxy RS232 Module

Operational features

- Instant display of incoming alarms
- Audiovisual indication of alarms
- Records and reports details of current and previous alarm events
- Background monitoring of alarms
- 250,000 event log
- Presents site details information
- Provides operator action instructions
- Provides contact telephone numbers
- 100 operator PIN assignments
- Option for single local site or multiple site monitoring
- Copy protection device (dongle) version available

PC REQUIREMENTS	SPECIFICATION
Operating System	Windows 98SE, 2000, ME, XP, NT4 with SP3
Processor	P3 600Mhz minimum
Memory	128MB minimum
Hard Disk Space	500MB minimum. More may be required depending on size of database
Comm Ports	1 or 2

* Some features are dependent on the model of Galaxy control panel used. The Galaxy 2 series system can't be used with event monitoring software.

Honeywell Security & Custom Electronics

Newhouse Industrial Estate
Motherwell
Lanarkshire
ML1 5SB
Tel +44 (0)1698 738200
Fax +44 (0)1698 738300
Literature +44 (0)870 240 3387

To reorder this literature,
call +44 (0)870 240 3387 quoting ref:
HSCE-GXPC-03-EN(0307)SB-C
March 2007
© 2007 Honeywell International Inc.

Honeywell