TECHNICAL SPECIFICATIONS	
POWER SUPPLY RATING	90V AC to 220V AC @ 65 W
PRIMARY SUPPLY	28.5V DC @ 2.4 A (Max.)
SECONDARY SUPPLY	21.7V DC to 27.2V DC; BAT charger: 28V DC
BATTERIES (INTERNAL)	2 x 12 V 7 AH
QUIESCENT CURRENT (NO DEVICES)	65 mA (4 Loop)
AUX. POWER OUTPUT	28V DC 300 mA
LOOPS	1 to 4 loops - Max 150 mA per loop
CONVENTIONAL SOUNDER CIRCUITS	2 - 500 mA Max. current drive per circuit - Fully monitored
AUX. RELAYS FIRE	2 rated 2A @ 30V DC resistive / 0.5A @ 120V AC / 0.25A @ 240V AC resistive
AUX. RELAY FAULT	1 rated 2A @ 30V DC resistive / 0.5A @ 120V AC / 0.25A @ 240V AC resistive
OPERATING / STORAGE TEMPERATURE	-10ºC to 50ºC
HUMIDITY	Max. 85% RH Non-Condensing
PROTECTION	Surface Mount: IP30, Recessed Mount: IP65
DIMENSIONS	273 (W) x 404 (H) x 107 (D) mm
WEIGHT	1.6 Kg - 7 Kg
COLOUR	White or Red

ORDER CODE	
GEKKO-1L	1 LOOP - PSU 2.4A
GEKKO-2L	2 LOOP - PSU 2.4A
GEKKO-3L	3 LOOP - PSU 2.4A
GEKKO-4L	4 LOOP - PSU 2.4A