VALKYRIE ASI

Addressable Wall Mount Sounder/ Beacon

The VALKYRIE AS is a Wall Mounted Addressable Sounder/ Beacon with low power consumption. Up to 32 individually addressed sounders can be installed per loop occupying address 94 to 125. The address is set using switches 1 to 5 of the 8 way DIL switch. Four different tones are available and selected using DIL switches 6 and 7.

When individual address reporting is not required, VALKYRIE AS can be configured as a Shadow Sounder. In this case sounders do not occupy an address in the loop thus freeing up addresses for more detection devices. Shadow sounders do not report back to the control panel so their presence on the loop is not monitored. Shadow sounders draw current from the loop (10 mA in alarm) and must be included in loop load calculations.

TECHNICAL SPECIFICATIONS		
SUPPLY VOLTAGE		Loop: 20 V to 30 V DC
LOOP CURRENT - QUIESCENT		0.5 mA
LOOP CURRENT - SOUNDER/ BEACON ACTIVE		10 mA - 280 mW @ 28 V DC inc. isolator
MAXIMUM SOUNDER OUTPUT		100 dB (@ 1 meter - 30 V DC)
MAX. CABLE SIZE		2.5 mm²
OPERATING TEMPERATURE		-10ºC to 55ºC
MAX. HUMIDITY		95% RH Non-Condensing
COLOUR / CASE MATERIAL		Red or White / ABS and PC
PROTECTION CATEGORY		IP21C - Type A - Indoor use
DIMENSIONS		110 (D) x 85 (H) mm inc. base
WEIGHT		254 g - inc. mounting base
ORDER CODE		
ALKYRIE ASI	1328-CPR-0286	ADDRESSABLE WALL SOUNDER WITH ISOLATOR
VALKYRIE ASBI	1328-CPR-0286	ADDRESSABLE WALL SOUNDER/ BEACON WITH ISOLATOR